

# SAMPA HEX

GLAZED PORCELAIN TILES

Crossville  
Studios

 DECORTILES

# SAMPA HEX

GLAZED PORCELAIN TILES

## SAMPA HEX FENDI



18x20,8cm | 7"x8"  
MA (MATTE)

## SAMPA HEX OFF WHITE



18x20,8cm | 7"x8"  
MA (MATTE)

## SAMPA HEX CINZA




18x20,8cm | 7"x8"  
MA (MATTE)

## SAMPA HEX CIMENTO



18x20,8cm | 7"x8"  
MA (MATTE)

### PRODUCT INFORMATION

| Type / Size   | Series    | Finish | Rectified | Unit | Work Size (mm) | Thick  | Faces | Sq. Ft./<br>Carton | Pieces/<br>Carton |
|---|-----------|--------|-----------|------|----------------|--------|-------|--------------------|-------------------|
|  Porcelain Tiles<br>18" x 20,8" | SAMPA HEX | Matte  | No        | SF   | 180 x 208      | 7,4 mm | 50    | 10,5               | 35                |

### USAGE RECOMMENDATION

|  | Target<br>DCOF wet | Suitable |
|--|--------------------|----------|
| Dry & Level - Interior Floor   | N/A                | ✓        |
| Wet & Level - Interior Floor   | ≥ 0.42             | ✓        |
| Shower Floors (Residential or Light Commercial)  | ≥ 0.42             | ✓        |
| Exterior Floor Applications<br>(including pool decking & other<br>wet areas with minimal footwear) | ≥ 0.60             |          |
| Ramps & Inclines   | ≥ 0.65             |          |
| Walls/Backsplashes - Interior  | N/A                | ✓        |
| Countertops  | N/A                | ✓        |
| Facades  | N/A                | ✓        |
| Pool Linings   | N/A                | ✓        |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

### QUALITY WARRANTY



Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).

### INSTALLATION AND CARE

Grout Joint Recommendation 1/8"

Shade Variation  V2 - SLIGHT VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less).

### PERFORMANCE CHARACTERISTICS

|                     | ASTM#                      | Result    |
|---------------------|----------------------------|-----------|
| Water Absorption    | C373                       | ≤ 0.5%    |
| Breaking Strength   | C648                       | ≥ 275 lbs |
| DCOF WET            | ANSI A137.1<br>ANSI A326.3 | ≥ 0.42    |
| Scratch Hardness    | MOHS                       | 3         |
| Frost Resistance    | C1026                      | Yes       |
| Chemical Resistance | C650                       | Class B   |
| Stain Resistance    | C1378                      | Class A   |



