

SOLOS

GLAZED PORCELAIN TILES





SOLOS

GLAZED PORCELAIN TILES

SOLOS SHELL



5x40 cm | 2"x16"
MA (MATTE)

SOLOS FENDI



5x40 cm | 2"x16"
MA (MATTE)

SOLOS ARGILA



5x40 cm | 2"x16"
MA (MATTE)

SOLOS TERRACOTA



5x40 cm | 2"x16"
MA (MATTE)

SOLOS HEX SHELL



18x20,8 cm | 7"x8"
MA (MATTE)

SOLOS HEX FENDI



18x20,8 cm | 7"x8"
MA (MATTE)

SOLOS HEX ARGILA



18x20,8 cm | 7"x8"
MA (MATTE)

SOLOS HEX TERRACOTA



18x20,8 cm | 7"x8"
MA (MATTE)



WALLS



FLOORS



SHOWERS
FLOORS



FIRE PROOF



VOC FREE





WATER
PROOF



SOLOS

GLAZED PORCELAIN TILES

PRODUCT INFORMATION

Type / Size	Series	Finish	Rectified	Unit	Work Size (mm)	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
 Porcelain Tiles 2" x 15,75"	SOLOS	Matte	No	SF	50 x 400	8 mm	100	8.6	40
 Porcelain Tiles 18" x 20,8"	SOLOS	Matte	No	SF	180 x 208	7,4 mm	50	10.5	35

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	✓
Wet & Level - Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior	N/A	✓
Countertops	N/A	✓
Facades	N/A	✓
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

QUALITY WARRANTY

QUALITY Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.

FIRE PROOF Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.

VOC FREE Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).

INSTALLATION AND CARE

Grout Joint Recommendation 2 mm
Shade Variation  V3 - MODERATE VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 275 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	≥ 0.42
Scratch Hardness	MOHS	3
Frost Resistance	C1026	Yes
Chemical Resistance	C650	Class B
Stain Resistance	C1378	Class A

